



Engine powered forklift 1.8 ton

Truck specifications					02-8FDF18
Identification	1.1	Manufacturer			TOYOTA
	1.2	Model			02-8FDF18
	1.3	Drive			Diesel
	1.4	Operator type			Rider seated
	1.5	Load capacity/rated load	Q	kg	1750
	1.6	Load centre	c	mm	500
	1.8	Load distance, centre of drive axle to fork	x	mm	410
	1.9	Wheelbase	y	mm	1485
	Weight	2.1	Service weight		kg
2.2		Axle load, with load, front/rear		kg	3940/540
2.3		Axle load, without load, front/rear		kg	1120/1610
Tyres	3.1	Tyre - pneumatic (P), pneumatic shaped cushion (SE), solid rubber (R)			SE
	3.2	Tyre size, front			6.50-10
	3.3	Tyre size, rear			5.00-8
	3.5	Wheels, number front/rear (x=driven wheels)			2x/2
	3.6	Track width, front	b_{10}	mm	885
	3.7	Track width, rear	b_{11}	mm	895
	Dimensions	4.1	Tilt of mast/fork carriage forward/backward	α/β	deg
4.2		Height, mast lowered	h_1	mm	1995
4.3		Free lift	h_2	mm	150
4.4		Lift	h_3	mm	2960
		Lift height	h_{23}	mm	3000
4.5		Height, mast extended	h_4	mm	4250
4.7		Height of overhead guard (cab)	h_6	mm	2080
4.8		Seat height	h_7	mm	1020
4.12		Coupling height	h_{10}	mm	285
4.19		Overall length	l_1	mm	3315
4.20		Length to face of forks	l_2	mm	2315
4.21		Overall width	b_1	mm	1070
4.22		Fork dimensions	s/e/l	mm	40/80/1000
4.23		Fork carriage DIN 15 173, class/type A, B			IIA
4.24		Fork-carriage width	b_3	mm	920
4.31		Ground clearance, with load, below mast	m_1	mm	80
4.32		Ground clearance, centre of wheelbase	m_2	mm	95
4.33		Aisle width for pallets 1000 x 1200 crossways	A_{st}	mm	3620
4.34	Aisle width for pallets 800 x 1200 lengthways	A_{st}	mm	3820	
4.35	Turning radius	W_a	mm	2010	
4.36	Internal turning radius	d_{13}	mm	575	
Performance data	5.1	Travel speed, with/without load		km/h	18,0/18,5
	5.2	Lift speed, with/without load		m/s	0,65/0,68
	5.3	Lowering speed, with/without load		m/s	0,50/0,55
	5.6	Max. drawbar pull, with/without load		N	16600/6300
	5.7	Gradeability, with load ^{1) 2)}		%	37
	5.8	Max. gradeability, with/without load ²⁾		%	41/20
	5.10	Service brake			Hydraulic
Engine combustion	7.1	Engine manufacturer/type			Toyota 1DZ-III (IIIA)
	7.2	Engine power acc. to ISO 1585		kW	36
	7.3	Rated speed		1/min	2400
	7.4	No. of cylinders/displacement		cm ³	4/2486
	7.5a	Fuel consumption according to VDI 60		l/h	3,0
	7.5b	Fuel consumption according to VDI 60		kg/h	—
Others	8.2	Operating pressure for attachments		bar	118
	8.3	Oil volume for attachments		l/min	64 max.
	8.4	Sound level at the driver's ear according to EN 12 053		dB(A)	79

¹⁾ At 1,5 km/h

²⁾ Computed values

Performance data and dimensions are nominal and subject to tolerances. Specifications are subject to change without notice.

Please obtain the latest specifications before contracting products.



Mast dimensions and rated

Model		V								FV					FSV							
8FG/DF15/18	Lift height	h_{23}	3000	330	350	370	400	450	500	550	3000	330	350	370	4000	430	4700	5000	5500	6000	6500	7000
	Lift	h_3	2960	326	346	366	396	446	496	546	2960	326	346	366	3960	426	4660	4960	5460	5960	6460	6960
	Height, mast lowered	h_1	1995	214	224	240	259	284	309	334	1995	214	224	240	2595	199	2145	2245	2405	2595	2845	3095
	Height, mast extended ¹⁾	h_4	3640	394	414	434	464	514	564	614	3590	389	409	429	4590	486	5265	5565	6065	6565	7065	7565
	Height, mast extended ²⁾	h_4	4250	455	475	495	525	575	625	675	4240	454	474	494	5240	554	5940	6240	6740	7240	7740	8240
	Free lift, without load backrest	h_2	150	150	150	150	150	150	150	150	144	159	169	185	204	146	1610	1710	1870	2060	2310	2560
	Free lift, with load backrest	h_2	150	150	150	150	150	150	150	150	785	935	103	119	1385	785	935	1035	1195	1385	1635	1885

1) Without load backrest

2) With load backrest; Height of standard load backrest is 1220 mm. Data in [] are for when "A4 piping" is selected.

Single tyre		V								FV					FSV							
8FG/DF18	Tilt range, forward	deg	6	6	6	6	6	6	6	—	6	6	6	6	6	6	6	6	6	6	6	—
	Tilt range, backward	deg	11(6)	11(6)	11(6)	11(6)	11(6)	6	6	—	11(6)	11(6)	11(6)	11(6)	11(6)	6	6	6	6	6	6	—
	Load capacity, P tyres at 500 mm LC	kg	1750	1750	1750	1750	1700	1600	155	—	1750	1750	1750	1750	1700	1550	1500	1450	110	850	50	—
	Load capacity, SE tyres at 500 mm LC	kg	1750	1750	1750	1750	1700	1600	155	—	1750	1750	1750	1750	1700	1550	1500	1450	120	950	57	—

Data in () are for when "Cabin Series" is selected (minimum front windshield).

